



KILGALLEN & PARTNERS

CONSULTING ENGINEERS

Kelland Homes

Zoning Submission Regarding Lands at Newtown Little & Newtownpark, Blessington, Co. Kildare

Flood Risk

Kelland Homes Kelland Homes Limited Russell Square Centre, Unit 5 Fortunestown Way, Tallaght, Dublin 24	Document Ref. No. 20003-OFR Issue 01	Kilgallen & Partners Consulting Engineers Well Road, Portlaoise Co. Laois
--	---	--

REVISION HISTORY

Client	Kelland Homes
Project	Zoning Submission Regarding Lands at Newtown Little & Newtownpark, Blessington, Co. Kildare
Title	Flood Risk

Date	Detail of Issue	Issue No.	Origin	Checked	Approved
23/05/22	Initial client issue	01	CP	PB	PB

TABLE OF CONTENTS

1.	Introduction	1
2.	Flood Risk at the Site Arising from Overland Flow	3
3.	Alternative Route for Overland Flow	4
3.1.	Calculation of overland flow rate	4
3.2.	Alternative Route for Overland Flow	5
4.	Development of the eastern side of the Site	6
4.1	Estimating Peak Flood Flows	6
4.2	Model	7
4.3	Existing Fluvial Flood Risk Zones at the Site	7
4.4	Compensatory Storage	8
4.5	Flood Risk Zones Post-Development	10
4.6	Conclusion	11
Appendix A	Flood Risk Map for Blessington Environs (extract from KCC Development Plan 2023 – 2029) CFRAM Flood Risk Map	
Appendix B	Estimation of Run-off from Catchment for Western Stream	
Appendix C	Details of Alternative Route for Overland Flow	
Appendix D	Estimation of Peak Flow in Catchment of Blessington Stream	

1. INTRODUCTION

Kelland Homes Ltd. [‘the Applicant’] is seeking an amendment to the draft Kildare County Development Plan 2023 – 2029 comprising the re-classification of lands [‘the Site’] at Newtown Little & Newtownpark, Blessington, Co. Kildare.

The extent of the Site and the streams located in or close to it are shown on Figure 1-1.




Figure 1-1 Site Location and Context

Figure 1-2 is reproduced from the draft County Development Plan and shows the land-use classification proposed at the Site. This proposed classification differs from the current development plan in that:

- an area of land, corresponding to a flow path for fluvial overland flow through the Site during extreme events, has been re-classified from New Residential to Amenity;
- all lands within the Site located east of the Blessington Stream and a corridor adjacent to the western boundary of the Blessington Stream have been re-classified from New Residential to Amenity;

This proposed classification severs the western part of the Site. This report proposes an alternative route for overland flow through the Site which would allow this severance to be eliminated (Sections 2 and 3 refer).

This proposed classification eliminates development in the eastern side of the Site. This report demonstrates that the eastern part of the Site can be developed in compliance with the Flood Risk Management Guidelines. (Section 4 refers).




Figure 1-2 Proposed Land-Use Classification

2. FLOOD RISK AT THE SITE ARISING FROM OVERLAND FLOW

CFRAM maps prepared for the CFRAM study programme flood risk from overland flow. The source of this overland flow is a watercourse [the Western Stream] which flows in a southerly direction to the west of the Site. The mapping suggests that during extreme rainfall events, the hydraulic capacity of the watercourse will be exceeded, and the exceedance water will flow overland to the western boundary of the Site. This overland flow pattern is similar to and consistent with the flood risk identified in the SFRA prepared for the draft County Development Plan 2023 – 2029. A copy of the relevant CFRAM flood risk map is provided in Appendix A.

Figure 2-1 shows the route for this overland flow through the Site.

The Western Stream is culverted at a point approximately 100m west of the Development Site. The culvert comprises a 450mm dia. pipe and is of lower hydraulic capacity than the channel / ponds upstream and downstream of it. This lower hydraulic capacity is the primary cause the overland flow which occurs upstream of the culvert.




Figure 2-1 Overland Flow Route

3. ALTERNATIVE ROUTE FOR OVERLAND FLOW

3.1. Calculation of overland flow rate

The catchment for the Western Stream is shown in Figure 3-1 and measures 0.76km².




Figure 3-1 Catchment of Watercourse west of Site

The OPW Web Portal advises particular caution where peak flows are being estimated for catchments of less than 25km². Accordingly, peak flows in the watercourse are estimated using IH124 (Flood Estimation for Small Catchments). Details of these calculations are included in Appendix B and the results summarised in Table 3-1. These estimates include a climate change factor of +20%. Table 3-1 also shows the equivalent peak flood flows as predicted by CFRAM. The CFRAM flows are higher and so, applying the precautionary principles, these higher flows are used for this assessment.

Return Period	Symbol	IH124 (m ³ /s)	CFRAM (m ³ /s)s
Mean Annual Average	Q _{bar}	0.32	
100 years (1% AEP)	Q ₁₀₀	1.04	1.36
1000 years (0.1% AEP)	Q ₁₀₀₀	1.38	2.40

Table 3-1 Peak Overland Flow (after applying 20% Climate Change Factor)

The piped culvert that restricts the capacity of the watercourse is 450mm dia. Based on the following conservative assumptions, the rate of overland flow through the Site is estimated to be 2.0m³/s.

- the headwater at the culvert inlet cannot exceed 1.0m, the culvert has a capacity of 0.4m³/s;
- during a 0.1% AEP event, all flow exceeding the capacity of the culvert becomes overland flow to the Development Site.

3.2. Alternative Route for Overland Flow

Figure 3-2 shows an alternative route for the overland flow risk at the Site. This alternative route is created by forming an open channel to the north of the existing route which has the capacity to carry the overland flow rate associated with the 0.1% AEP event.

Details of the alternative overland flow route are provided in Appendix C.

The alternative route is selected to be as close to the northern boundary of the Site as possible and thus minimise the severance caused by the need to accommodate this overland flow risk.




Figure 3-2 Alternative Route for Overland Flow

4. DEVELOPMENT OF THE EASTERN SIDE OF THE SITE

A preliminary design for development of the Site was prepared in 2003 [referred to hereafter as 'the Development']. As part of the design process, an initial assessment of flood risk was carried out in accordance with the Flood Risk Management Guidelines. This initial assessment identified indicators of fluvial flood risk at the Site and so detailed assessment of fluvial flood was carried out.

4.1 Estimating Peak Flood Flows

The catchment area for the stream, shown on Figure 4-1, measures 6.48 km².



Figure 4-1 Catchment Area for Stream

The OPW provides a Web Portal for estimating peak flood flows in natural catchments (Flood Studies Update (FSU) Web Portal). While the use of this Portal is generally considered best practice for the estimation of flood flows, the Portal advises particular caution where peak flows are being estimated for catchments of less than 25km². Accordingly, peak flows in the stream are estimated using IH124 (Flood Estimation for Small Catchments). Details of these calculations are included in Appendix D and the results summarised in Table 4-1. These estimates include a climate change factor of +20%.

Table 4-1 also shows the equivalent peak flood flows as predicted by CFRAM. The CFRAM flows are slightly higher and so, applying the precautionary principles, these higher flows are used for this assessment.

Return Period	Symbol	IH124 (m ³ /s)	CFRAM (m ³ /s)
Mean Annual Average	Q _{bar}	0.478	
100 years (1% AEP)	Q ₁₀₀	6.99	7.01
1000 years (0.1% AEP)	Q ₁₀₀₀	9.28	9.68

Table 4-1 Peak Fluvial Flows (after applying 20% Climate Change Factor)

4.2 Model

A topographical survey was carried out for the study area by a third-party land surveyor. The results of this survey were imported into the industry standard software package Infrastructure Ultimate Design Suite to create a 3D digital terrain model for the study area.

A hydrological model was prepared to simulate flow patterns during the 100 year and 1000 year rainfall events. This model was developed using the River and Flood Analysis module of the industry standard package Infrastructure Ultimate Design Suite produced by Autodesk. The hydrological modelling within this module is itself based on the HEC-RAS modelling software produced by the US Army Corps of Engineers.

The module calculates flood risk zones for the catchment based on the peak flood flows and the following:

- the terrain model;
- cross-sectional data for the river channel;
- dimensions of culverts and other drainage structures;
- appropriate values for the roughness coefficient 'Manning's n' as determined from visual inspection of the Development Site.

The flow volumes in Table 4-1 significantly exceed the capacity of the 1200mm dia. culvert into which the stream discharges at the southern boundary. Surcharged water will overtop the wall at the southern boundary when the surcharged water level reaches 194.80m. The model therefore assumes a downstream water level of 194.80m.

4.3 Existing Fluvial Flood Risk Zones at the Site

Figure 4-2 contains a map showing the existing fluvial flood risk zones determined using the hydrological model described above superimposed on the emerging layout for the Development.. Peak water levels are as follows:

- 1.0% AEP Flood Event 194.80m
- 0.1% AEP Flood Event 194.82m




Figure 4-2
Existing Flood Risk Zones Associated with Blessington Stream superimposed on the Development Layout

4.4 Compensatory Storage

While the layout of the Development is broadly cognisant of fluvial flood risk, elements of the proposed development, in particular roads, encroach on the flood risk zones. This creates the potential for the proposed development to displace floodplain storage and thereby increase flood risk elsewhere. To prevent this, it is necessary to provide compensatory storage within the Site. Compensatory storage is provided by reducing the existing ground level immediately adjacent to the stream to create a basin. Figure 4-3 shows the general layout of the two compensatory storage areas that are proposed.

The requirements for providing compensatory storage are set out in the Appendix to the Flood Risk Management Guidelines. Normally it is calculated by comparing volumes taken by the development and the volume offered by the compensatory storage for a number of horizontal slices through the range defined above - the thickness of a slice should be typically 0.1 metres.

The compensatory volume should be at the same level (within reasonable working limits) as the lost storage for each slice. Compensatory storage cannot be located in an area where water-vulnerable development is proposed.




Figure 4-3 Compensatory Storage Basins

The industry standard package Infrastructure Ultimate Design Suite (by Autodesk) was used to create surface models for the existing site and for the finished level of the proposed development. Comparison models were then created using these surfaces.

Table 4-2 presents the results of this modelling and shows that for nearly all elevation intervals, the volume of compensatory storage provided actually exceeds the volume of floodplain storage displaced. There is loss of floodplain at only the highest levels. Cumulatively, significantly more floodplain storage will be available upon completion of the proposed development than is currently available, thereby reducing fluvial flood risk elsewhere.

Elevation (m OD)	Storage Available		Change in Storage
	Pre-Development	Post-Development	
193.00	663	799	136
193.10	754	1,645	891
193.20	853	1,703	850
193.30	956	1,749	793
193.40	1,060	1,789	729
193.50	1,164	1,828	664
193.60	1,277	1,875	598
193.70	1,426	1,937	511
193.80	1,562	2,016	454
193.90	1,703	2,109	406
194.00	1,821	2,171	350
194.10	1,931	2,224	293
194.20	2,041	2,270	229
194.30	2,164	2,312	148
194.40	2,309	2,353	44
194.50	2,489	2,394	-95
194.60	2,716	2,436	-280
194.70	2,995	2,490	-505
194.80	3,277	2,570	-707
Cumulative change in Storage			5,509

Table 4-2 Available Floodplain Storage : Pre- and Post-Development

4.5 Flood Risk Zones Post-Development

Figure 4-4 shows the flood risk zones associated with the Stream Post-Development. Flood Risk zones are confined to open spaces and do not encroach on water-vulnerable elements of the proposed development. Peak water levels are effectively the same as pre-development:

- 1.0% AEP Flood Event 194.81m
- 0.1% AEP Flood Event 194.82m






Figure 4-4 Flood Risk Zones Associated with Blessington Stream - Post-Development

4.6 Conclusion

The detailed assessment demonstrates that development of the eastern part of the Site is possible while achieving full compliance with the Flood Risk Management Guidelines.

Appendix A

**Flood Risk Map for Blessington Environs (extract from SFRA for draft
Development Plan 2023 – 2029)**



Legend

- Flood Zone A - 1 % AEP Flood Extent
(1 in 100 chance in any given year)
- Flood Zone B - 0.1% AEP Flood Extent
(1 in 1000 chance in any given year)
- Indicative Flood Extents
- Defended Area
- Flood Risk Assessment
- County Boundary

Client
**Kildare
County
Council**



Project
**Strategic Flood
Risk Assessment**



Title
Blessington Environs

RPS
West Pier Business Campus,
Dun Laoghaire,
Co. Dublin
Ireland
T +353 (0)1 4882900
F +353 (0)1 462 0814
E ireland@rpsgroup.com
W rpsgroup.com/ireland

Issue Details	
Drawn by:	RK
Checked by:	BT
Approved by:	SK
Scale:	1:10,000 @ A3
Date:	13/09/2016
Project No.:	MDW0710
File Ref.:	MDW0710/MI0014F01
Drawing No.:	MI0014
Rev.:	F01

Notes
1. This drawing is the property of RPS Group Ltd. It is a confidential document and must not be copied, used, or its contents divulged without prior written consent.
2. Ordnance Survey Ireland Licence EN 0005016
© Copyright Government of Ireland.

CFRAM Flood Risk Map



IMPORTANT USER NOTE:
 THE VIEWER OF THIS MAP SHOULD REFER TO THE DISCLAIMER, GUIDANCE NOTES AND CONDITIONS OF USE THAT ACCOMPANY THIS MAP.

- Legend**
- 10% Fluvial AEP Event
 - 1% Fluvial AEP Event
 - 0.1% Fluvial AEP Event
 - Modelled River Centreline
 - AFA Extents
 - Node Point
 - Node ID

FINAL

REV:	NOTE:	DATE:
------	-------	-------



The Office of Public Works
 Jonathan Swift Street
 Trim
 Co Meath

Elmwood House
 74 Boucher Road
 Belfast
 BT12 6RZ

T +44(0) 28 90 667914
 F +44(0) 28 90 668286
 W www.rpsgroup.com
 E ireland@rpsgroup.com

Map:
 Blessington Fluvial Flood Extent Maps

Map Type: EXTENT

Source: FLUVIAL

Map Area: HPW

Scenario: CURRENT

Drawn By: F.M.C. **Date:** 26 July 2016

Checked By: T.D. **Date:** 26 July 2016

Approved By: S.P. **Date:** 26 July 2016

Drawing No. :
E09BLE_EXFCD_F0_02

Map Series : 2 of 4

Drawing Scale : 1:5,000 @A3


Node Label	Water Level (OD)		Flow (m³/s)		Water Level (OD)		Flow (m³/s)	
	10% AEP	1% AEP	10% AEP	1% AEP	0.1% AEP	1% AEP	0.1% AEP	
09DPAR00238I	197.81	2.13	198.04	3.97	198.60	6.73		
09DPAR00202I	195.60	2.45	195.72	4.63	195.81	7.84		
09DPAR00193	194.75	3.97	194.96	6.17	195.12	9.35		
09DPAR00186	194.44	4.08	194.66	8.06	194.83	13.13		
09DPAR00176	193.82	4.16	194.31	8.63	194.48	15.29		
09DPAR00155	193.68	3.56	194.29	7.01	194.45	9.68		
09DPAR00109	189.51	N/A	190.02	N/A	190.30	N/A		
09NWPk00071I	201.06	N/A	202.65	N/A	205.03	N/A		
09NWPk00071mI	195.76	0.27	196.11	1.25	196.82	3.21		
09LTNT00128	219.97	0.31	220.04	0.58	220.12	1.03		
09LTNT00073	204.60	0.72	204.72	1.36	204.78	2.40		
09LTNT00063J	201.86	N/A	201.86	N/A	201.86	N/A		
09NWPk00000kI	199.44	N/A	199.66	N/A	200.23	N/A		
09NWPk00000oI	195.43	1.30	195.84	2.34	196.08	4.16		
09NWPk00001cI	200.39	N/A	200.83	N/A	201.48	N/A		

Appendix B
Estimation of Run-off from Catchment for Western Catchment



Estimation of Q_{100} For Blessington SSFRA - IH124

Characteristic	Value	Unit	Source
Area (A)	0.8	km ²	FSU
Average Annual Rainfall (SAAR)	966	mm	
G1 % =	0	%	Fig I 4.18
G2 % =	100	%	Fig I 4.18
G3 % =	0	%	Fig I 4.18
G4 % =	0	%	Fig I 4.18
G5 % =	0	%	Fig I 4.18
Soil index (G) =	0.30	%	
$Q_{BAR RURAL}$ =	0.19	m ³ /sec	
CWI =	123		Fig I 6.62
CIND =	30.16		Eqn 7.2
NC =	0.69		Eqn 7.3
URBAN =	20.0	%	
$Q_{BAR URBAN} / Q_{BAR RURAL}$ =	1.387		Eqn 7.4
Q_{BAR} =	0.268	m ³ /sec	
Q_{100} / Q_{BAR} (Ireland)	1.96		FSR - Ireland
$Q_{1,000} / Q_{BAR}$ (Ireland)	2.6		FSR - Ireland
Q_{100} =	0.524	m ³ /sec	
$Q_{1,000}$ =	0.696	m ³ /sec	
Factorial Error Factor =	1.651		Page 37 IOH124
Climate Change Factor =	1.2		GSDSDS
Q_{100} =	1.04	m³/sec	
$Q_{1,000}$ =	1.38	m³/sec	

Appendix C
Details of Alternative Route for Overland Flow



LHS Side-slope (1V:)	Bed Width	Channel			Design Flow	Results	
		RHS Side-slope (1V:)	min. gradient	n		Depth of Flow	Flow Velocity
H	m	H	0.50%	0.03	(m ³ /s)	(m)	(m/s)
2.00	2.00	5.00	0.50%	0.03	2.00	0.49	1.11



Profile Through Channel for Alternative Overland Flow Route
Scale H 1:1000 V 1:100

OS mapping reproduced under licence.
This drawing is not to be reproduced without the written permission of Kilgallen and Partners. Copyright.

REV	DATE	BY	DETAILS

STATUS
FOR ZONING SUBMISSION PURPOSES ONLY. NOT TO BE USED FOR ANY OTHER PURPOSE.

CLIENT
KELLAND HOMES LTD.

PROJECT
ZONING SUBMISSION FOR LANDS AT NEWTOWN LITTLE & NEWTOWNPARK, BLESSINGTON, CO. KILDARE

TITLE
Alternative Overland Flow Route

KILGALLEN & PARTNERS
CONSULTING ENGINEERS
KYLEKIPROE, WELL ROAD, PORTLAOISE, CO. LAOIS
Tel: +353 56 77 0190, Fax: +353 56 770 5077
E-mail: Info@kilgallen.ie, Web: www.kilgallen.ie

DEN: SC	DRAWING NO.: 20003-OFR-01	REV.: 00
CHKD: PB	SCALE: as shown @ A1	DATE: 23/05/22

Appendix D
Estimation of Peak Flow in Catchment of Blessington Stream

Estimation of Q_{100} For Blessington SSFRA - IH124

Characteristic	Value	Unit	Source
Area (A)	6.5	km ²	FSU
Average Annual Rainfall (SAAR)	966	mm	
G1 % =	0	%	Fig I 4.18
G2 % =	100	%	Fig I 4.18
G3 % =	0	%	Fig I 4.18
G4 % =	0	%	Fig I 4.18
G5 % =	0	%	Fig I 4.18
Soil index (G) =	0.30	%	
$Q_{BAR RURAL}$ =	1.30	m ³ /sec	
CWI =	123		Fig I 6.62
CIND =	30.16		Eqn 7.2
NC =	0.69		Eqn 7.3
URBAN =	20.0	%	
$Q_{BAR URBAN} / Q_{BAR RURAL}$ =	1.387		Eqn 7.4
Q_{BAR} =	1.801	m ³ /sec	
Q_{100} / Q_{BAR} (Ireland)	1.96		FSR - Ireland
$Q_{1,000} / Q_{BAR}$ (Ireland)	2.6		FSR - Ireland
Q_{100} =	3.529	m ³ /sec	
$Q_{1,000}$ =	4.682	m ³ /sec	
Factorial Error Factor =	1.651		Page 37 IOH124
Climate Change Factor =	1.2		GSDSDS
Q_{100} =	6.99	m³/sec	
$Q_{1,000}$ =	9.28	m³/sec	